

## Compressor Bock<sup>1</sup> FKX40 and FKX50 Bus Air Conditioning

## World class performance, compact and robust design

The product of extensive experience in the transport refrigeration and air conditioning market, the Bock FKX40 and FKX50 open drive compressor models offer world class performance and durability. The 4 cylinder FKX40 and

6 cylinder FKX50 are available in a variety of displacement levels and can be sized to meet a wide range of applications. The Bock Compressors offer many valued features sought after in the transport air conditioning market.



FKX40




FKX50

## **Features**

- High efficiency and reliable operation
- Lightweight and compact aluminum design
- Robust lubrication system and bearings
- Forced-feed lubrication
- Proven shaft seal designed for long life and ease of service
- Optimized for R134a, R407C
- Special K-valve plate optimized for air conditioning applications
- Practical drain through a feely accessible flexible tube (no dismantling of the clutch necessary)

MCC • July 2014 PN: 89-3063



## **Technical Data**

	Bock <sup>1</sup> FKX40	Bock <sup>1</sup> FKX50
Rotation	CW/CCW	CW/CCW
Max speed	3500 rpm	3500 rpm
Clutch coil	24 VDC	24 VDC
Displacement	39.7 in <sup>3</sup> (650 cm <sup>3</sup> /rev)	50.7 in <sup>3</sup> (830 cm <sup>3</sup> )
Number of cylinders	4	6
Refrigerant	R134a, R407C	R134a, R407C
Pulleys	2-SPB, 2 – 5 V	2-SPB, 2 – 5 V
Oil charge	67.6 oz (2000 cm³)	67.6 oz (2000 cm³)
Dimensions (L x W x H)	15.2" (386.08 mm) x 12.8" (325.12 mm) x 14.6" (370.84 mm)	16.9" (429.26 mm) x 14.8" (375.92 mm) x 13.2" (335.28 mm)
Weight (without clutch)	73 lbs (33 kg)	93 lbs (42 kg)

<sup>1)</sup> Bock Compressors are now part of the Global GEA Companies

